

BACKGROUND OF THE INVENTION

5

The present invention relates to a system and method for controlling intake air to an internal combustion engine by variable valve timing.

2. Terminology

10

This is used herein to mean the sum of displacements of all of cylinders of an engine. "Engine displacement" and "displacement of an engine" are synonyms. In the description, the reference character "VOL#" is used to represent the "engine displacement".

3. Description of Related Art

JP-A 8-200025 discloses a system for controlling electromagnetic drivers (EMDs) for intake and exhaust valves provided per each combustion chamber of an internal combustion engine. According to this system, an electronic control unit (ECU) controls valve timings of intake and exhaust valves independently from the crankshaft position and speed in one of predetermined schedules fit for various engine operation ranges. The ECU identifies which one of the various engine operation ranges against varying engine load and engine speed. During transient period from one to another of the engine operation ranges, the ECU shifts the valve timings of intake valves in a gradual manner so as to prevent occurrence of a rapid change in intake air characteristic. This JP-A is silent as to how engine load is controlled and has no teaching with regard to engine load control by early or delayed valve closure timings of the intake valves.

The present invention aims at controlling intake air by

1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300
2301
2302
2303
2304
2305
2306
2307
2308
2309
2310
2311
2312
2313
2314
2315
2316
2317
2318
2319
2320
2321
2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429
2430
2431
2432
2433
2434
2435
2436
2437
2438
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
2461
2462
2463
2464
2465
2466
2467
2468
2469
2470
2471
2472
2473
2474
2475
2476
2477
2478
2479
2480
2481
2482
2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
2512
2513
2514
2515
2516
2517
2518
2519
2520
2521
2522
2523
2524
2525
2526
2527
2528
2529
2530
2531
2532
2533
2534
2535
2536
2537
2538
2539
2540
2541
2542
2543
2544
2545
2546
2547
2548
2549
2550
2551
2552
2553
2554
2555
2556
2557
2558
2559
2560
2561
2562
2563
2564
2565
2566
2567
2568
2569
2570
2571
2572
2573
2574
2575
2576
2577
2578
2579
2580
2581
2582
2583
2584
2585
2586
2587
2588
2589
2590
2591
2592
2593
2594
2595
2596
2597
2598
2599
2600
2601
2602
2603
2604
2605
2606
2607
2608
2609
2610
2611
2612
2613
2614
2615
2616
2617
2618
2619
2620
2621
2622
2623
2624
2625
2626
2627
2628
26

5

10

25

30

2025-11-11

and the undesired torque change during transient period from one to the other of the two intake air controls is suppressed.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a system
5 and method for controlling intake air to an internal combustion
engine such that the occurrence of violent torque variation
caused by aggressive cyclic depression and release manipulation
of an accelerator pedal is prevented and the undesired torque
change during transient period from one to the other of the two
10 intake air controls is suppressed.

According to one aspect of the present invention there is provided a method for controlling intake air of an internal combustion engine, the engine having at least one combustion chamber provided with intake means together with an intake manifold provided with a throttle valve, wherein the opening and closure timings of the intake means are adjustable entirely independently from the crankshaft position to control the amount of intake air supplied to the combustion chamber, the method comprising:

20 *providing a response adjustment to variable valve timing*
 control of the intake means for unthrottled intake air control.

According to another aspect of the present invention, there is provided a system for controlling intake air of an internal combustion engine, the engine having at least one combustion chamber provided with intake means together with an intake manifold provided with a throttle valve, wherein the opening and closure timings of the intake means are adjustable entirely independently from the crankshaft position to control the amount of intake air supplied to the combustion chamber, the method comprising:

a control for a response adjustment to variable valve timing control of the intake means for unthrottled intake air control.

[illegible]

Figure 1 is a block diagram illustrating a system and method for controlling intake air to an internal combustion engine according to the present invention.

Figure 3 is a block diagram of a control unit implementing the present invention.

Figure 5 is a graph illustrating intake air control schedule.

Figure 7 is a graphical representation of retrievable mapped date of values of intake valve closure (IVC) timing of intake means against varying values of target airflow rate.

Figure 9 is a schematic representation of retrievable mapped data of response correction coefficient represented by the reference character FLOAD.

Figures 11A, 11B and 11C are graphical representations illustrating engine response performance with the benefit of the present invention as compared to engine response performance without the benefit of the present invention.

Figure 1 is a block diagram illustrating operation of a system or method for controlling intake air by variable intake

Engine 12 includes various other sensors such as a
30 crankshaft sensor or engine speed sensor 54, which provides a
signal indicative of engine speed (NE) to C/U 14, and an engine
coolant temperature sensor 56. Engine coolant temperature
sensor 56 provides an engine coolant temperature (T_w) signal

[illegible]

indicative of the engine coolant temperature to C/U 14.

Figure 2 provides a schematic view of an EMD 86, which is used in each of valve controls 34 and 38, for the associated cylinder valve, for example, intake valve 32. EMD 86 includes a housing 88, a movable plate 90 is kept in a neutral position, as illustrated in Figure 2, within housing 88 by means of two springs 92 and 94. Springs 92 and 94 are arranged on one and the opposite sides of movable plate 90. At the remotest ends, springs 92 and 94 bear against housing 88. At the nearest ends, springs 92 and 94 bear against spaced walls of movable plate 90. Two electromagnetic coils 96 and 98 are mounted to housing 88 on one and the opposite sides of movable plate 90. With no supply of electric current through electromagnetic coil 98, supply of electric current through electromagnetic coil 96 attracts movable plate 90 for movement against the action of spring 92. Supply of electric current through electromagnetic coil 98 with no supply of electric current through electromagnetic coil 96 attracts movable plate 90 for movement against the action of spring 94. In order to transmit at least movement of movable plate 90 in a direction against spring 94 to intake valve 32, the valve stem is operatively connected to movable plate 90. Thus, with no supply of electric current through electromagnetic coil 96, supply of electromagnetic coil 98 can hold intake valve 32 lifted from a rest position where intake valve 32 rests on a valve seat 102. In this embodiment, valve stem 100 is fixed to movable plate 90 so that supply of electric current through electromagnetic coil 96 with interruption of supply of electric current through electromagnetic coil 98 can hold intake valve 32 to the rest position.

Referring to Figure 3, C/U 14 receives signals from the various sensors via input ports 104, which may provide signal conditioning, conversion, and/or fault detection as well known in

the art. Input ports 104 communicate with processor (MPU) 106 via a data/control bus 108. MPU 106 implements control logic in the form of hardware and/or software instructions, which may be stored in a computer-readable media 110 to effect intake air control for engine 12. Computer-readable media 110 may include various types of volatile and nonvolatile memory such as random-access memory (RAM) 112, read-only memory (ROM) 114, and keep-alive memory (KAM) 116. These functional classifications of memory may be implemented by one or more different physical devices such as PROMs, EPROMs, EEPROMs, flash memory, and the like, depending upon the particular application.

Sub MPU 106 communicates with various actuators of engine 12 via output ports 118. Actuators may control ignition timing or spark SPK, timing and metering of fuel FIV, position of throttle valve TVA to control air inflow, intake valve timing (IVT) to control intake air into combustion chamber and exhaust valve timing (EVT). In operation range where throttled intake air control is required, the position of throttle valve 44 is variably adjusted by an actuator in the form of a motor 45 to control intake air into combustion chamber 16 and intake valve closure (IVC) timing is adjusted by EMD 86 to provide a valve opening duration in the neighborhood of the least duration. In operation range where unthrottled intake air control is required, IVC control is performed and the position of throttle valve 44 is adjusted so as to maintain boost pressure within intake manifold at a target negative pressure value. In IVC control, intake valve closure (IVC) timing is variably adjusted to control intake air into combustion chamber 16 without relying on throttling of airflow by throttle valve 44.

Figure 5 illustrates, by a shadowed area, low-load high-speed operation range where throttled intake air control is to be performed. An area not shadowed in Figure 5 illustrates

operation range where throttled intake air control is to be performed.

In the low-load high-speed operation range, it is impossible to accomplish a target intake air by early valve closure timing because the minimum valve opening duration is determined independently of the crankshaft position and speed by EMD 86.

With the minimum valve opening duration having the earliest valve closure timing, increasing the crankshaft speed results in a delay in valve closure timing in terms of crankshaft angular position. Thus, in the low-load high-speed operation range as indicated by the shadowed area in Figure 5, it is impossible to accomplish the target intake air by early intake valve closure with the wide open throttle (WOT).

In a preferred embodiment, in operation range not shadowed in Figure 5, unthrottled intake air control is performed to accomplish a target value by variably adjusting IVC timing with boost pressure within intake manifold 26 maintained constant by variably adjusting throttle valve 44. In low-load high-speed operation range as indicated by shadowed area in Figure 5, throttled intake air control is performed to accomplish a target value by variably adjusting throttle position of throttle valve 44 to vary the boost pressure with the IVC timing adjusted in the neighborhood of the minimum valve opening duration.

Sub 3 In the preferred embodiment, MPU 106 executes instructions stored in computer-readable media 110 to carry out a method for intake air control to communicate with EMD 34 of for intake valve 32 and motor 45 for throttle valve 44 for unthrottled intake air control in coordination with throttled intake air control.

Figure 4 provides a block diagram illustrating representative controllers for intake air control to provide engine torque control.

In the preferred embodiment, C/U 14 implements determination of a target intake air (TQH0SH) at a block 120 based on operator torque request command derived from accelerator position VAPO and engine speed NE. A group of curves 122 in Figure 6 illustrate how target intake air TQH0SH varies against variation of VAPO at each of different values of engine speed NE. One representative example of determination of TQH0SH is disclosed in United States Patent Application Serial No. Unassigned yet, filed on December 2, 2000, entitled "Unthrottled intake air control with partial delay for requested engine response performance," which has been commonly assigned herewith and claims the priority of Japanese Patent Applications Nos. 11-343910 (filed December 2, 1999), 11-345375 (filed December 3, 1999), 11-345374 (filed December 3, 1999), and 11-356401 (filed December 15, 1999). The disclosure of this commonly assigned pending United States Patent Application has been hereby incorporated by reference in its entirety to clarify one example of processing, which may be performed at block 120. Another example of processing, which may be performed at block 120, is a table look-up operation of retrievable mapped data as illustrated in Figure 6, stored in ROM 114, against various combination of values of VAPO and NE to determine a target value of TQH0SH. In this case, an intake air amount need for idle speed control (IDS) should be added to the target value obtained by the table look-up operation.

Block 120 provides its output TQH0SH to a block 124. Block 124 inputs NE as well as TQH0SH and performs control mode selection. Block 124 compares the input value of TQH0SH with a threshold value on a curve 126 defining the boundary of the part-load high-speed operation range illustrated by the shadowed area in Figure 5. For obtaining the threshold value on curve 126, a table look-up operation of mapped data of values in intake air on curve 126 against the input value of NE. The

mapped data of threshold values is stored in ROM 114. In block 124, unthrottled intake air control is selected if TGH0SH holds a predetermined relation with threshold value 126. The predetermined relation involves TGH0SH greater than threshold value 126. Block 124 selects throttled intake air control if
 5 TGH0SH fails to hold the predetermined relationship. For example, throttled intake air control is selected when TGH0SH is less than threshold value 126.

Assuming now that unthrottled intake air control is
 10 selected, block 124 provides TQH0SH to a block 130 for determination of TVA for unthrottled intake air control and also to a block 134 for determination of IVC for unthrottled intake air control.

For determination of TVA for throttled intake air control in
 15 block 130, MPU 106 determines a target throttle position TVA in the neighborhood of wide open throttle (WOT) position so that inflow of air to intake manifold 26 is held unthrottled.

For determination of IVC for throttled intake air control in block 134, MPU 106 determines IVC timing by performing a table
 20 look-up operation of mapped retrievable values on a curve 136 shown in Figure 7 against the input value of FQH0SH. Block 134 provides determined IVC to a response adjustment block 128. Figure 8 provides a mathematical representation of processing performed at block 128 using IVC and response correction
 25 coefficient FLOAD. Values of FLOAD are determined based on data obtained by various experiments or tests or by computer simulations to provide an appropriate delay equivalent to the time constant caused by the volume of the intake manifold 26 downstream of throttle valve 44. Figure 9 illustrates structure of
 30 retrievable data of values of FLOAD including a number of two-dimensional maps, called FLOAD maps, prepared against representative values of engine speed NE (RPM). Against the input value of NE, two maps are selected for table look-up

001027 1552260

operations against the current input value of IVC and the preceding or old value of the processed or final target intake valve closure timing FIVCOLD to provide two retrieved values. Using these two retrieved values, an interpolation is made to an appropriate value of FLOAD against the current value of NE. In the illustration, only one set of FLOAD maps are used to provide FLOAD. Preferably, different sets of FLOAD maps should be provided and used for acceleration and deceleration, respectively.

As illustrated in Figure 18, using as inputs IVC and FLOAD, block 128 generates, as an output, FIVC by calculating the following equation:

$$FIVC = IVC \times FLOAD + FIVCOLD \times (1 - FLOAD) \dots (1).$$

where: FIVCOLD is an old or preceding value of FIVC.

Block 128 provides FIVC to a control loop for EMD 34. The control loop determines a control signal in response to FIVC and provides the control signal to EMD 34 for closing intake valve 32 at the closure timing as indicated by determined IVC timing.

In the preferred embodiment, the valve opening and valve closure timings of intake valve 32 for throttled intake air control are such that the valve opening timing is held at a crankshaft position near the top dead center (TDC) and the valve closure timing is variably shifted to a crankshaft position falling within a range between the crankshaft position of the valve opening timing and the bottom dead center (BDC).

Let us now assume that throttled intake air control mode is selected in block 124. In this case, block 124 provides TQH0SH to block 138 for determination of TVA for throttled intake air control mode. Concurrently with the selection of throttled intake air control mode, a block 140 for determination of IVC for throttled intake air control mode is triggered to put into

2025 FEB 11 11 55 AM '05

In Figure 10, step 150 represents input of VAPO. Step 152
30 represents input of NE. Step 154 represents determination of
TQH0SH. Step S156 represents input of NE. Step 158
represents determination of IVC for throttled intake air control.
Step 160 represents response adjustment in the manner as

Referring to Figures 11A, 11B and 11C, the fully drawn line in each of Figures 11B and 11C illustrates a smooth transient response characteristic with the benefit of the present invention in response to a step-like increase of VAPO as illustrated in Figure 14A. The dotted line in each of Figures 11B and 11C illustrates a transient response characteristic without the benefit of the present invention.

$$FQH0ST = (TQH0SH \times FLOAD + FQHOLD \times (1 - FLOAD)) \dots (2).$$

While the present invention has been particularly described, in conjunction with preferred embodiment, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art in light of the foregoing description. It is therefore contemplated that the appended claims will embrace any such alternatives, modifications and variations as falling within the true scope and spirit of the present invention.

This application claims the priority of Japanese Patent Application No. 11-345374, filed December 3, 1999, the disclosure of which is hereby incorporated by reference in its entirety.